

M20LED EVO M16LED EVO



CON RIFLETTORE INTERCAMBIABILE



45° Reflector



25° Reflector



MARINOCRISTAL®
 Via Guardia Del Consiglio, 29/31
 47899 Serravalle
 Repubblica di San Marino
 t.+378 0549 901188
 fax.+378 0549 900612
 www.marinocrystal.com
 marinocrystal@marinocrystal.com

M20LED EVO

codice code	W W	W W	V V	attacco base	colore colour	lumen360°/cd lumen360°/cd	lumen90° lumen90°	FP PF	fascio beam	Colore del corpo body colour	imballo packing
21402	20	194(ERP)	220-240	GU10	3000°K	1580/2357	1530	>0.5	25°/45°	BIANCO/WHITE	10/50
21408	20	201(ERP)	220-240	GU10	4000°K	1630/2466	1580	>0.5	25°/45°	BIANCO/WHITE	10/50
21403	20	194(ERP)	220-240	GU10	3000°K	1580/2357	1530	>0.5	25°/45°	GRIGIO/GREY	10/50
21409	20	201(ERP)	220-240	GU10	4000°K	1630/2466	1580	>0.5	25°/45°	GRIGIO/GREY	10/50
21404	20	194(ERP)	220-240	GU10	3000°K	1580/2357	1530	>0.5	25°/45°	NERO/BLACK	10/50
21410	20	201(ERP)	220-240	GU10	4000°K	1630/2466	1580	>0.5	25°/45°	NERO/BLACK	10/50

M20LED EVO

codice code	W W	W W	V V	attacco base	colore colour	lumen360°/cd lumen360°/cd	lumen90° lumen90°	FP PF	fascio beam	Colore del corpo body colour	imballo packing
21399	20	194(ERP)	I2AC/DC	G53	3000°K	1580/2357	1530	>0.5	25°/45°	BIANCO/WHITE	10/50
21405	20	201(ERP)	I2AC/DC	G53	4000°K	1630/2466	1580	>0.5	25°/45°	BIANCO/WHITE	10/50
21400	20	194(ERP)	I2AC/DC	G53	3000°K	1580/2357	1530	>0.5	25°/45°	GRIGIO/GREY	10/50
21406	20	201(ERP)	I2AC/DC	G53	4000°K	1630/2466	1580	>0.5	25°/45°	GRIGIO/GREY	10/50
21401	20	194(ERP)	I2AC/DC	G53	3000°K	1580/2357	1530	>0.5	25°/45°	NERO/BLACK	10/50
21407	20	201(ERP)	I2AC/DC	G53	4000°K	1630/2466	1580	>0.5	25°/45°	NERO/BLACK	10/50

MI 6LED EVO

codice code	W W	W W	V V	attacco base	colore colour	lumen360°/cd lumen360°/cd	lumen90° lumen90°	FP PF	fascio beam	Colore del corpo body colour	imballo packing
21412	16	137(ERP)	220-240	GU10	3000°K	1190/2055	1150	>0.5	25°/45°	BIANCO/WHITE	10/50
21411	16	143(ERP)	220-240	GU10	4000°K	1230/2201	1190	>0.5	25°/45°	BIANCO/WHITE	10/50
21414	16	137(ERP)	220-240	GU10	3000°K	1190/2055	1150	>0.5	25°/45°	GRIGIO/GREY	10/50
21397	16	143(ERP)	220-240	GU10	4000°K	1230/2201	1190	>0.5	25°/45°	GRIGIO/GREY	10/50
21413	16	137(ERP)	220-240	GU10	3000°K	1190/2055	1150	>0.5	25°/45°	NERO/BLACK	10/50
21398	16	143(ERP)	220-240	GU10	4000°K	1230/2201	1190	>0.5	25°/45°	NERO/BLACK	10/50

MI 6LED EVO DIMMERABILE

codice code	W W	W W	V V	attacco base	colore colour	lumen360°/cd lumen360°/cd	lumen90° lumen90°	FP PF	fascio beam	Colore del corpo body colour	imballo packing
21421	16	123(ERP)	220-240	GU10	3000°K	1090/2055	1060	>0.5	25°/45°	BIANCO/WHITE	10/50
21422	16	123(ERP)	220-240	GU10	3000°K	1090/2055	1060	>0.5	25°/45°	GRIGIO/GREY	10/50
21423	16	123(ERP)	220-240	GU10	3000°K	1090/2055	1060	>0.5	25°/45°	NERO/BLACK	10/50



MI 6LED EVO

codice code	W W	W W	V V	attacco base	colore colour	lumen360°/cd lumen360°/cd	lumen90° lumen90°	FP PF	fascio beam	Colore del corpo body colour	imballo packing
21418	16	137(ERP)	I2AC/DC	G53	3000°K	1190/2055	1150	>0.5	25°/45°	BIANCO/WHITE	10/50
21417	16	143(ERP)	I2AC/DC	G53	4000°K	1230/2201	1190	>0.5	25°/45°	BIANCO/WHITE	10/50
21419	16	137(ERP)	I2AC/DC	G53	3000°K	1190/2055	1150	>0.5	25°/45°	GRIGIO/GREY	10/50
21415	16	143(ERP)	I2AC/DC	G53	4000°K	1230/2201	1190	>0.5	25°/45°	GRIGIO/GREY	10/50
21420	16	137(ERP)	I2AC/DC	G53	3000°K	1190/2055	1150	>0.5	25°/45°	NERO/BLACK	10/50
21416	16	143(ERP)	I2AC/DC	G53	4000°K	1230/2201	1190	>0.5	25°/45°	NERO/BLACK	10/50