

STRIP LED 2835 IP20_9.6W



Code	21948/24
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	NDLS
Light source cap-type (or other electric interface):	
Mains or non-mains (MLS / NMLS):	NMLS
Dimmable:	yes
On-mode power (Pon), expressed in W	4,6 (W)
Energy consumption (kWh/1000 h)	5 (kWh/1000h)
Energy efficiency class	G
Useful luminous flux (Φuse)	396 in sphere (360°)
Correlated colour temperature K	3000K



Height	1,2 (mm)
Width	8 (mm)
Depth	5000 (mm)
Claim of equivalent powerc	-
If yes, equivalent power (W)	if yes, data (W) required
Chromaticity coordinates (x and y)	X 0,4339 Y 0,4033
Peak luminous intensity (cd)	Not applicable (cd)
Beam angle in degrees, or the range of beam angles that can be set	115 (°)
R9 colour rendering index value	2
Survival factor	0,9
Lumen maintenance factor	0,96
displacement factor (cos φ1)	Not applicable
Colour consistency in McAdam ellipses	5
Flicker metric (Pst LM)	Not applicable
Stroboscopic effect metric (SVM)	No Applicable



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocristal.com
marinocristal@marinocristal.com



