

GOCCIALED D DIMMABILE



Code	21098
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	NDLS
Light source cap-type (or other electric interface):	E27
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	yes
On-mode power (Pon), expressed in W	9 (W)
Energy consumption (kWh/1000 h)	9 (kWh/1000h)
Energy efficiency class	F
Useful luminous flux (Φuse)	900 in sphere (360°)
Correlated colour temperature K	2700

Height	110 (mm)
Width	60 (mm)
Depth	60 (mm)
Claim of equivalent power	yes / -
If yes, equivalent power (W)	65 (W)
Chromaticity coordinates (x and y)	
X	0,459
Y	0,412
Peak luminous intensity (cd)	not relevant (cd)
Beam angle in degrees, or the range of beam angles that can be set	not relevant (°)
R9 colour rendering index value	2
Survival factor	0,9
Lumen maintenance factor	0,96
displacement factor (cos φ1)	0,5
Colour consistency in McAdam ellipses	5
Flicker metric (Pst LM)	1
Stroboscopic effect metric (SVM)	0,4



MARINO CRISTAL SPA

Via Guardia del Consiglio, 29/31

47899 - Serravalle

REPUBBLICA DI SAN MARINO

TEL +378 0549 901188

FAX +378 0549 900612

www.marinocristal.com

marinocristal@marinocristal.com

