

HI-EFFICIENCY STRIP LED 2835 IP20



Code	21960/24
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	NDLS
Light source cap-type (or other electric interface):	
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	yes
On-mode power (Pon), expressed in W	13,4 (W)
Energy consumption (kWh/1000 h)	14 (kWh/1000h)
Energy efficiency class	E
Useful luminous flux (Φuse)	1814 in sphere (360°)
Correlated colour temperature K	3000



Height	1 (mm)
Width	10 (mm)
Depth	5000 (mm)
Claim of equivalent power	-
If yes, equivalent power (W)	93 (W)
Chromaticity coordinates (x and y)	
X	0,44
Y	0,402
Peak luminous intensity (cd)	not relevant (cd)
Beam angle in degrees, or the range of beam angles that can be set	120 (°)
R9 colour rendering index value	2
Survival factor	0,9
Lumen maintenance factor	0,96
displacement factor (cos φ1)	0,7
Colour consistency in McAdam ellipses	3
Flicker metric (Pst LM)	
Stroboscopic effect metric (SVM)	



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocrystal.com
marinocrystal@marinocrystal.com

