

# HI-EFFICIENCY STRIP LED 2835 IP20



|                                                      |                      |
|------------------------------------------------------|----------------------|
| Code                                                 | 21954/24             |
| Lighting technology used:                            | LED                  |
| Non-directional or directional (NDLS / DLS):         | NDLS                 |
| Light source cap-type (or other electric interface): |                      |
| Mains or non-mains (MLS / NMLS):                     | NMLS                 |
| Dimmable:                                            | yes                  |
| On-mode power (Pon), expressed in W                  | 8,16 (W)             |
| Energy consumption (kWh/1000 h)                      | 9 (kWh/1000h)        |
| Energy efficiency class                              | F                    |
| Useful luminous flux (Φuse)                          | 950 in sphere (360°) |
| Correlated colour temperature K                      | 4000K                |



|                                                                    |                           |
|--------------------------------------------------------------------|---------------------------|
| Height                                                             | 1,4 (mm)                  |
| Width                                                              | 10 (mm)                   |
| Depth                                                              | 5000 (mm)                 |
| Claim of equivalent powerc                                         | -                         |
| If yes, equivalent power (W)                                       | if yes, data (W) required |
| Chromaticity coordinates (x and y)                                 | X 0,373<br>Y 0,367        |
| Peak luminous intensity (cd)                                       | Not applicable (cd)       |
| Beam angle in degrees, or the range of beam angles that can be set | 120 (°)                   |
| R9 colour rendering index value                                    | 12                        |
| Survival factor                                                    | 0,9                       |
| Lumen maintenance factor                                           | 0,96                      |
| displacement factor (cos φ1)                                       | Not applicable            |
| Colour consistency in McAdam ellipses                              | 5                         |
| Flicker metric (Pst LM)                                            | Not applicable            |
| Stroboscopic effect metric (SVM)                                   | Not applicable            |



MARINO CRISTAL SPA  
Via Guardia del Consiglio, 29/31  
47899 - Serravalle  
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188  
FAX +378 0549 900612  
[www.marinocristal.com](http://www.marinocristal.com)  
[marinocristal@marinocristal.com](mailto:marinocristal@marinocristal.com)



