TUBILED T8 25 _120LM/W PF0.5



Code	21627	
Lighting technology used:	LED	
Non-directional or directional (NDLS / DLS):	NDLS	
Light source cap-type (or other electric interface):		G13
Mains or non-mains (MLS / NMLS):	MLS	
Dimmable:	no	
On-mode power (Pon), expressed in W	25	(W)
Energy consumption (kWh/1000 h)	25	(kWh/1000h)
Energy efficiency class	E	
Useful luminous flux (Φuse)	3000	in sphere (360°)
Correlated colour temperature K	4000	

Height		28	(mm)
Width		1500	(mm)
Depth		1500	(mm)
Claim of equivalent powerc		-	
If yes, equivalent power (W)			(W)
Chromaticity coordinates (x and y)			
	X	0,32	
	Y	0,345	
Peak luminous intensity (cd)		not relevant	(cd)
Beam angle in degrees, or the range of beam angles that can be set		not relevant	(°)
R9 colour rendering index value		2	
Survival factor		0,9	
Lumen maintenance factor		0,95	
displacement factor (cos φ1)		0,7	
Colour consistency in McAdam ellipses		5	
Flicker metric (Pst LM)		1	
Stroboscopic effect metric (SVM)		0,4	

WARRANTY 2 YEARS

INSTANT

RoHS Compliant

CE

MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocristal.com
marinocristal@marinocristal.com



