

# T38LED 15\_HIGH EFFICIENCY



|                                                      |                       |
|------------------------------------------------------|-----------------------|
| Code                                                 | 21586                 |
| Lighting technology used:                            | LED                   |
| Non-directional or directional (NDLS / DLS):         | NDLS                  |
| Light source cap-type (or other electric interface): | E27                   |
| Mains or non-mains (MLS / NMLS):                     | MLS                   |
| Dimmable:                                            | no                    |
| On-mode power (Pon), expressed in W                  | 15 (W)                |
| Energy consumption (kWh/1000 h)                      | 15 (kWh/1000h)        |
| Energy efficiency class                              | D                     |
| Useful luminous flux (Φuse)                          | 2200 in sphere (360°) |
| Correlated colour temperature K                      | 2700                  |

|                                                                    |                   |
|--------------------------------------------------------------------|-------------------|
| Height                                                             | 150 (mm)          |
| Width                                                              | 38 (mm)           |
| Depth                                                              | 38 (mm)           |
| Claim of equivalent power                                          | yes / -           |
| If yes, equivalent power (W)                                       | 136 (W)           |
| Chromaticity coordinates (x and y)                                 |                   |
| X                                                                  | 0,44              |
| Y                                                                  | 0,403             |
| Peak luminous intensity (cd)                                       | not relevant (cd) |
| Beam angle in degrees, or the range of beam angles that can be set | not relevant (°)  |
| R9 colour rendering index value                                    | 2                 |
| Survival factor                                                    | 0,9               |
| Lumen maintenance factor                                           | 0,96              |
| displacement factor (cos φ1)                                       | 0,7               |
| Colour consistency in McAdam ellipses                              | 5                 |
| Flicker metric (Pst LM)                                            | 1                 |
| Stroboscopic effect metric (SVM)                                   | 0,4               |



MARINO CRISTAL SPA  
Via Guardia del Consiglio, 29/31  
47899 - Serravalle  
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188  
FAX +378 0549 900612  
[www.marinocristal.com](http://www.marinocristal.com)  
[marinocristal@marinocristal.com](mailto:marinocristal@marinocristal.com)

