

ELLISSOLED_EVO



Code	21651
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	NDLS
Light source cap-type (or other electric interface):	
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	no
On-mode power (Pon), expressed in W	40 (W)
Energy consumption (kWh/1000 h)	40 (kWh/1000h)
Energy efficiency class	E
Useful luminous flux (Φuse)	5200 in sphere (360°)
Correlated colour temperature K	4000

Height	228 (mm)
Width	96 (mm)
Depth	96 (mm)
Claim of equivalent power	yes / -
If yes, equivalent power (W)	287 (W)
Chromaticity coordinates (x and y)	
X	0,38
Y	0,38
Peak luminous intensity (cd)	0 (cd)
Beam angle in degrees, or the range of beam angles that can be set	0 (°)
R9 colour rendering index value	2
Survival factor	0,9
Lumen maintenance factor	0,96
displacement factor (cos φ1)	0,9
Colour consistency in McAdam ellipses	3
Flicker metric (Pst LM)	1
Stroboscopic effect metric (SVM)	0,9



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocristal.com
marinocristal@marinocristal.com

