CONSTANT CURRENT 4,32W_STRIP LED 2835



Code	21971/24	
Lighting technology used:	LED	
Non-directional or directional (NDLS / DLS):	NDLS	
Light source cap-type (or other electric interface):		
Mains or non-mains (MLS / NMLS):	NMLS	
Dimmable:	yes	
On-mode power (Pon), expressed in W	2,3	(W)
Energy consumption (kWh/1000 h)	3	(kWh/1000h)
Energy efficiency class	F	
Useful luminous flux (Φuse)	232	in sphere (360°)
Correlated colour temperature K	3000K	

Height		1,2	(mm)
Width		8	(mm)
Depth		5000	(mm)
Claim of equivalent powerc		-	
If yes, equivalent power (W)		if yes, data required	(W)
Chromaticity coordinates (x and y)			
	X	0,4339	
	Y	0,4033	
Peak luminous intensity (cd)		Not applicable	(cd)
Beam angle in degrees, or the range of beam angles that can be set		115	(°)
R9 colour rendering index value		2	
Survival factor		0,9	
Lumen maintenance factor		0,96	
displacement factor (cos φ1)		Not applicable	
Colour consistency in McAdam ellipses		5	
Flicker metric (Pst LM)		Not applicable	
Stroboscopic effect metric (SVM)		No Applicable	



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocristal.com
marinocristal@marinocristal.com

