

GOCCIALED



Code	21271
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	NDLS
Light source cap-type (or other electric interface):	E27
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	no
On-mode power (Pon), expressed in W	8 (W)
Energy consumption (kWh/1000 h)	8 (kWh/1000h)
Energy efficiency class	E
Useful luminous flux (Φ_{use})	910 in sphere (360°)
Correlated colour temperature K	4000

Height	105 (mm)	
Width	60 (mm)	
Depth	60 (mm)	
Claim of equivalent powerc	yes / -	
If yes, equivalent power (W)	66 (W)	
Chromaticity coordinates (x and y)	X	0,44
	Y	0,403
Peak luminous intensity (cd)	not relevant (cd)	
Beam angle in degrees, or the range of beam angles that can be set	not relevant (°)	
R9 colour rendering index value	2	
Survival factor	0,9	
Lumen maintenance factor	0,95	
displacement factor (cos ϕ 1)	0,5	
Colour consistency in McAdam ellipses	5	
Flicker metric (Pst LM)	1	
Stroboscopic effect metric (SVM)	0,4	



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocrystal.com
marinocrystal@marinocrystal.com

