

PAR30LED TUTTOVETRO



Code	21353
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	DLS
Light source cap-type (or other electric interface):	
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	no
On-mode power (Pon), expressed in W	10 (W)
Energy consumption (kWh/1000 h)	
A	
Useful luminous flux (Φuse)	
Correlated colour temperature K	



Depth	97 (mm)
L70B50	20000 hours
Claim of equivalent powerc	NO
yes	
X	0,44
Y	0,403
Parameters for directional light sources:	
Peak luminous intensity (cd)	700 (cd)
Beam angle in degrees, or the range of beam angles that can be set	50 (°)
Parameters for LED and OLED light sources:	(°)
Lumen maintenance factor	0,95
Parameters for LED and OLED mains light sources:	
displacement factor (cos φ1)	0,5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattaged	-
Colonna1	
Total calculations performed with the parameters, including the detemination of the energy efficiency class	
factors total mains (FTM)	1,176



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocrystal.com
marinocrystal@marinocrystal.com

